

**EXPO 500 PT R134A
(COD. E1785S0000)**



Ventilated open upright display

Technical data

Temperature	+2°C +8°C
Voltage and Frequency	230 Volt 50 Hz
Gas	R134a
Net dimension	668 x 685 x 1990 mm (w x d x h)
Packed dimension	755 x 705 x 2100 mm (w x d x h)
Gross capacity	472 dm ³
Net capacity	353 dm ³
Gross weight	118 Kg
Net weight	106 Kg
Heat insulation	In polyurethane injected "HCFC/CFC" free
External cabinet	White prepainted non-toxic steel sheet
Cabinet back	Galvanized steel sheet
Inner tank	White prepainted non-toxic steel sheet
Door frame - colour	White prepainted aluminium
Glass	Thermoinsulating
Handle	Grey plastic
Light box - colour	White plastic
Light box opaline	Back lighted white opale plastic
Frontal grid - colour	White plastic
Compressor	1/4 hp
Power consumption	350 Watt
Condensator	Packed condensation system (finned) with powered fan
Evaporator	Packed system (finned) with powered fan
Climatic class - EN 441	4 (30°C 55% R.H.)
Plug	European - Angular Plug
Thermometer	Mechanic
Thermostat	Mechanic
Inner shelves	5 Removable
Standard equipment	2 one-way wheels + 2 adjustable feet
Optional	Door closure with lock key on control panel
Producer brand	FRAMEC

The manufacturer will reserve the right to make any modification without prior notice.

Version	Updated on	Written by	Approved by
2	17/10/2007	D. Capuano	R. Bovo