## FRESH PV 60 R134A (COD. EBM070415)



## Upright display cooler

Temperature	+1°C +8°C			
Voltage and Frequency	230 Volt 50 Hz			
Gas	R134a			
Net dimension	775 x 730 x 1865 mm (w x d x h)			
Packed dimension	830 x 810 x 1965 mm (w x d x h)			
Gross capacity	640 dm³			
Net capacity	600 dm³			
Gross weight	115 Kg			
Net weight	107 Kg			
Heat insulation	In polyurethane injected "HCFC/CFC" free			
External cabinet	White painted sheet			
Cabinet back	Galvanized steel sheet			
Inner tank	White thermoformed plastic			
Door frame - colour	White prepainted aluminium			
Glass	29 mm insulating glasses			
Handle	White plastic (built in the door frame)			
Handle insert				
Control board cover	White plastic			
Frontal grid - colour	White painted sheet			
Compressor	1/4 hp			
Power consumption	340 Watt			
Condensator	Static condensation system (fan assisted)			
Evaporator	Packed evaporation system (finned) with powered fan			
Climatic class - EN 441	4 (30°C 55% R.H.)			
Plug	European - Angular Plug			
Thermometer	Mechanic			
Thermostat	Mechanic			
Inner shelves	White plastified shelves - 5 removable GN 2/1 + 1 in the bottom of the tank			
Standard equipment	Internal light			
Optional	Lock - Wheels - Legs			
Producer brand	FRAMEC			

he manufacturer will reserve the right to	Version	Updated on	Written by	Approved by
hake any modification without prior notice.	1	19/10/2007	D. Canuano	R Boyo